

PERSONAL PROTECTIVE EQUIPMENT

2919 MSA Bump Cap
> with flap

BC Prochoice Bump Cap
> without flap

2905 Sweat Bands
> pack of 20
> to suit 2903 & 2904 Hardhats

2927 Sweat Band
> lambswool

2906 VM Kit
> safety cap, earmuffs & mesh visor
> complete protection in one package

3130 Browguard with Earmuffs & Visor
> rating class 5 SLC₈₀ value 27
> clear visor
> lightweight combination



BROWGUARD & VISOR

2901 Assembled Browguard & Visor
> anti-fog visor and browguard
> 99.9% UV protection for outdoor wear



VC Visor only - Clear
> polycarbonate visor
> 450mm W x 205mm H

VS Visor only - Smoked
> anti-fog 2mm
> high impact
> 99.9% UV protection
> 450mm W x 205mm H

Vs5 Visor only - Shade 5
> anti-fog 2mm
> certified to AS/NZS 1338 ID 4018 for gas welding

2928 Visor Holder
> attaches to hard hat to hold visor

2907 Browguard with Visor
> ratchet browguard with visor

2930 Visor Holder
> general & high temperature use

2931 Peaked Visor Holder
> with brim



| FACE PROTECTION SYSTEM | | | | | UNISAFE VISOR SELECTION | | | | | | |
|------------------------|---------------------------------|--------------|-------------|-----------------------|-------------------------|---------|---------------|-------------|----------|------------|---------------------------|
| Brow Guard | Safety Cap Visor Carrier | Visor Code | Material | Size HxW | Chin Guard | Outdoor | Medium Impact | High Impact | Chemical | Hot Solids | Radiant Heat Metal/Splash |
| | W997 | VH500 series | VM820 | Mesh* | 150x300mm | | | | | | |
| | | | W931 | PC, clear | 200x300mm | | ✓ | ✓ | | ✓ | |
| | | | W848 | PC, clear | 200x300mm | | ✓ | | ✓ | ✓ | ✓ |
| | | | W730 | PC, clear, unbound | 200x380mm | | ✓ | | ✓ | ✓ | ✓ |
| | | | W602M | Mesh brass | 200x300mm | | | | | | ✓ |
| | | | W932 | PC, clear | 200x400mm | | ✓ | ✓ | | ✓ | ✓ |
| | | | W876 | T, clear | 200x400mm | | ✓ | ✓ | | ✓ | ✓ |
| | | | W501 | PC, clear, unbound | 225x400mm | ✓ | ✓ | | ✓ | ✓ | ✓ |
| | | | W511 | T, clear, unbound | 225x400mm | ✓ | ✓ | ✓ | | ✓ | ✓ |
| | | | W515 | T, shade 5 | 225x400mm | ✓ | ✓ | ✓ | | ✓ | ✓ |
| | | | W502 | PC, clear gold plated | 225x400mm | ✓ | | | ✓ | | ✓ |
| | | | W882 | T, clear | 250x400mm | | ✓ | ✓ | | ✓ | ✓ |
| | | | W854 | PC, clear | 200x400mm | | ✓ | | ✓ | ✓ | ✓ |
| | | | W904 | PC, green shade 5 | 250x400mm | | ✓ | | ✓ | ✓ | ✓ |
| | | | W925 | PC, clear | 250x400mm | | ✓ | | ✓ | ✓ | ✓ |
| | | W926 | PC, shade 5 | 250x400mm | | ✓ | | ✓ | ✓ | ✓ | |
| | Complete carrier & visors VC105 | W848 | PC, clear | 200x300mm | | ✓ | | ✓ | ✓ | ✓ | |

All Eye & face protection products are certified to AS/NZS 1337. It is recommended that all visors be worn with secondary protection such as safety spectacles or goggles

* Mesh = AS/NZS 1337 does not require mesh visors to be tested. Mesh visors recommended for low impact only

PC = Polycarbonate, temp range = 70 to 105 degrees celsius. Very resistant to impact & waterbased liquids (biological, acids, weak solvents).

T = Thermotuff, temp range = 90 to 125 degrees celsius. Delamination warns of over heating. Excellent performance against wide range of chemicals

Visors & Browguards

INDUSTROQUIP



1300 303 249



1300 366 584



www.industroquip.com